

UWR B150 水下射灯





12/24V DC	IP 68	Class III	Ra>80	CE	RoHS	Ik 08
PWM	1-10 V	Dali	2000 K	3000 K	6000 K	RGB

UWR B150
 High quality underwater luminaire , it is suitable for water attractions, sculpture, fountains etc;
 Temperature of water between -20°C~40°C less than 1 meter depth;
 Built-in overheat sensor system, Automatic Shutdown at 75°C;

Housing is made of molding shaped hard chromeplated stainless steel SUS 316L# ;
 8 mm PMMA enclosure;
 Silicone gasket;
 IP68 PG-11 copper with nickel-coated;
 Power cable Ho7RN-F (RGB 4×1.0 mm²), L=3.0m;
 Options: PWM / 1-10V / Dali;
 2000k / 3000k / 6000k / RGB;
 Beam angle;

UWR B150 水下射灯
 高品质水下照明灯具，适用于水景、雕塑、喷泉等照明；
 产品适用不大于1米水深、-20°C~40°C的水温环境；
 产品具有75°C过温保护功能；

316L不锈钢灯体，表面镀铬处理；
 8 mm 厚 PMMA 灯罩；
 硅胶密封圈；
 IP68 PG-11 电缆锁头，预留2×1.0 mm² (RGB 4×1.0 mm²)电缆，长度3米；
 可选项包括: PWM / 0-10 V / Dali;
 2000 k / 3000 k / 6000 k / RGB ；
 光束角



UWR B150 Guide

UWR B150 订货指南

Article No. 产品编号	Product Name 产品名称	Description 描述	Optics 光学系统	LED Lamps LED 光源
				38.4 W
9 887 04 01		DC 12 / 24 V 12×3 W 单色leds 9° 光束角 IP68 IKo8	LS-9	
9 887 04 02		DC 12 / 24 V 12×3 W 单色leds 15° 光束角 IP68 IKo8	LS-15	
9 887 04 03		DC 12 / 24 V 12×3 W 单色leds 20° 光束角 IP68 IKo8	LS-20	
9 887 04 04		DC 12 / 24 V 12×3 W 单色leds 30° 光束角 IP68 IKo8	LS-30	
9 887 04 05	UWR B 150	DC 12 / 24 V 12×3 W 单色leds 45° 光束角 IP68 IKo8	LS-45	
9 887 04 06		DC 12 / 24 V 12×3 W 单色leds 60° 光束角 IP68 IKo8	LS-60	
9 887 04 21		DC 12 / 24 V 6×5 W RGB 三合一 leds 20° 光束角 IP68 IKo8	LS-20	
9 887 04 22		DC 12 / 24 V 6×5 W RGB 三合一 leds 30° 光束角 IP68 IKo8	LS-30	

Order No.: Article No. + Lamp (Colour Temperature) , Driver and controllers need to be purchased separately
 订货方式: 产品编号+光源（色温），驱动电源、控制器等需要另外选购

